



**Description:**

Rubber end caps for usage with Flexalen 600 and Flexalen SL for watertight closure between carrier pipe and corrugated casing. Carrier pipe exits are reduced for variable combinations of carrier pipes

**Technical details:**

MATERIAL

Rubber quality	EPDM 40 +/- 5
Colour	black
Shore A	40 +/- 5° ShA
Temperature range	-40°C up to +70°C

Product code	Outer casing O.D. [mm]	N° pipes	Carrier pipe(s) O.D. [mm]	Weight [kg]
VS-MAN40A20-A16	40	1	16, 20	0,025
VS-MAN50A25-A20	50	1	20, 25	0,029
VS-MAN63A32-A16	63	1	16, 20, 25, 32	0,043
VS-MAN75A40-A16	75	1	16, 20, 25, 32, 40	0,075
VS-MAN90A50-A20	90	1	20, 25, 32, 40, 50	0,095
VS-MAN125A75-A32	125	1	32, 40, 50, 63, 75	0,180
VS-MAN160A90-A50	160	1	50, 63, 75, 90	0,220
VS-MAN200A125-A110	200	1	110, 125	0,225

Product code	Outer casing O.D. [mm]	N° pipes	Carrier pipe(s) O.D. [mm]	Weight [kg]
VS-MAN63A2/20-A2/16	63	2	16, 20	0,045
VS-MAN75A2/20-A2/16	75	2	16, 20	0,055
VS-MAN90A2/25-A2/16	90	2	16, 20, 25	0,080
VS-MAN125A2/32-A2/20	125	2	20, 25, 32	0,185
VS-MAN160A2/50-A2/32	160	2	32, 40, 50	0,205
VS-MAN200A2/63	200	2	63	0,225